



SAFETY DATA SHEET

1. Product Identification

Champion Brands, LLC
1001 Golden Drive
Clinton, MO 64093
(660) 885-8151

Product line: CHAMPION® Diesel Flo® Diesel Conditioner and De-icer
Products: 4183
CAS: Mixture
Synonyms: Distillate fuel flow improver
Recommended use: Distillate fuel additive
Restrictions: Do not use near heat/sparks/open flames.
Created: 21 July 21, 2014
Revised: 22 July 2014
Emergency phone: CHEMTREC: (+1) 800-424-9300

2. Hazards Identification

Appearance: Clear, colorless liquid
Odor: Mild hydrocarbon odor
Classification(s): Flammable Liquid, Category 2
 Aspiration Hazard, Category 1
 Skin Irritation, Category 2
 Eye Irritation, Category 2
 Aquatic Toxicity (Chronic), Category 2
 Aquatic Toxicity (Acute), Category 2
 Specific Target Organ Toxicity – Single Exposure, Category 3

Target organs: CNS – narcotic effects

Symbol(s):



Signal Word: DANGER

Hazard Statement(s): Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

- Other hazard(s):** Repeated exposure may cause dryness of the skin
- Precaution(s):** Keep away from heat/sparks/open flames/hot surfaces – no smoking. Take precautionary measures against static discharge. Do not breathe mist/vapors/spray. Use in a well ventilated area. Wear protective gloves/protective clothing. Do not ingest. IF SWALLOWED: Do NOT induce vomiting. Get immediate medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Disposal:** Keep out of waterways. Check local, national, and international regulations for proper disposal

3. Composition/Information on Ingredients

Hazardous Ingredients:

<i>Component</i>	<i>CAS No.</i>	<i>Conc (wt%)</i>
Distillates, petroleum, hydrotreated, light	64742-47-8	60 – 70
Acrylic copolymer	Trade secret	15 – 30
2-Propanol	67-63-0	10 – 20
Solvent naphtha (petroleum), heavy aromatic, kerosene	64742-94-5	10 – 20
Naphthalene	91-20-3	< 3
2-Ethylhexyl nitrate	27247-96-7	< 3

4. First Aid Measures

- Eyes** Remove contact lenses, if worn. Rinse with running water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention if irritation persists.
- Skin** Remove affected clothing and launder before reuse. Wash affected area for at least 15 minutes with soap and running water. Seek medical attention if persistent irritation occurs. Prolonged or repeated exposure may cause defatting of the skin – symptoms include redness, dryness, cracking
- Inhalation** Remove exposed person to fresh air immediately. Restore or assist breathing, if necessary. Get medical attention if breathing is slow or difficult.

Ingestion	If swallowed DO NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to minimize the chance of aspiration. If fever, shortness of breath, congestion, coughing or wheezing occurs, get immediate medical attention.
Additional Info Specific Treatments	Note to physician: High potential for chemical pneumonitis! Consider gastric lavage with protected airway, or administration of activated charcoal. Call poison control for specific guidance.

5. Fire Fighting Measures

NFPA (estimated): **Health – 2** **Fire – 3** **Instability – 0**

Flash Point >12°C / 54°F

Extinguishing Media Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment.

Unsuitable Media Do not use water jet

Firefighting Procedures: Keep nearby containers cool with water spray.

Unusual Hazards Low flash point – significant potential for flash fires. Material will flow over water pools and may cause fire to spread. Incomplete combustion can produce carbon monoxide.

6. Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures:

Flammable liquid – can cause flash fires from a significant distance to a source of ignition. Keep unnecessary personnel away. Wear appropriate personal protective equipment for emergency. Ventilate if released in a confined area. Eliminate sources of ignition if it is safe to do so.

Environmental precautions: Avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways or groundwater

Methods for removal: Use an explosion-proof pump to remove bulk liquid. Residual liquid can be absorbed on inert material or evaporated with adequate ventilation. **Use only non-sparking tools.**

7. Handling and Storage

Max. Handling Temp: Do not store or handle at elevated temperatures. See Section 5 for flammability and Section 10 for chemical stability

Procedures: Use only in a well ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Use appropriate containment to avoid environmental contamination. Vapors are heavier than air and will tend to accumulate in low areas. Avoid sources of ignition and use non-sparking tools. Avoid use in confined areas without adequate ventilation. Areas of inadequate ventilation could contain concentrations high enough to cause eye irritation, headaches, or nausea. Avoid breathing dust, fume, gas, mist, vapors, or spray. Wash thoroughly after handling. Launder contaminated clothing before reuse. Empty container contains product residue which may exhibit hazards of the product. Do not weld, heat, or pressurize empty containers. Do not re-use containers. Dispose of packaging or containers in accordance with local, regional, national, and international regulations. Store away from strong oxidizers

Max Store Temp: Do not store or handle at elevated temperatures.

Unsuitable Materials: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Other: Store in a diked area and prevent discharge into the aquatic environment

8. Exposure Controls/Personal Protection

Exposure Limits

US

Guidelines by component

Distillates, petroleum, hydrotreated, light (CAS # 64742-47-8)

ACGIH: 200 mg/m³ (TWA)

2-Propanol (CAS # 67-63-0)

ACGIH: 200 ppm (TWA)

ACGIH: 400 ppm (STEL)

OSHA: 400 ppm / 980 mg/m³ (TWA)

OSHA: 500 ppm / 1,225 mg/m³ (STEL)

NIOSH: 400 ppm / 980 mg/m³ (TWA)

NIOSH: 500 ppm / 1,335 mg/m³ (STEL)

Naphthalene (CAS # 91-20-3)

ACGIH: 10 ppm / 52mg/m³ (TWA)

ACGIH: 15 ppm / 79mg/m³ (STEL)

OSHA: 10 ppm / 50 mg/m³ (TWA)

1,2,4-Trimethylbenzene (CAS # 95-63-6)

ACGIH: 25 pm / 123 mg/m³ (TWA)

2-Ethylhexyl nitrate (CAS # 27247-96-7)

OSHA (OEL): 1ppm, 8 hours (TWA)

Other Exposure Limits: Not determined

Engineering Controls: Use in a well ventilated area. Local and general ventilation should keep methanol vapor concentration below permissible limits. Where exposure potential exceeds recommended limits, use a NIOSH/OSHA approved supplied air respirator as recommended. Vapors are heavier than air and will tend to accumulate in low-lying areas.

Personal Protective Equipment

Respiratory:

Use a positive-pressure supplied-air NIOSH approved respirator when used in confined spaces or where engineering controls are not sufficient to limit exposure to below recommended limits

Eye:

Face shield or chemical splash goggles when splashing may occur. If possible, remove contact lenses before handling

Gloves:

Use neoprene or viton gloves. Nitrile gloves can be used – but prolonged contact may cause the rubber to degrade

Clothing:

Use chemical resistant pants and jackets

Other:

Locate the nearest eyewash station and safety shower before handling this product. Limit exposure whenever possible. Consider flammability and always use non-sparking tools.

Hygiene:

Wash thoroughly after handling this product.

9. Physical and Chemical Properties

Appearance

Clear, colorless to pale yellow liquid

Odor

Mild hydrocarbon or alcoholic odor

Odor threshold	Not determined
pH	Not determined
Melting Point	Not determined
Initial Boiling Pt	Not determined
Flash Point	12.0°C / 53.6°F (minimum; most flammable component))
Evaporation Rate	Not determined
Upper Flammable Lm	Not determined
Lower Flammable Lm	Not determined
Explosive Data	Vapors of this product may form explosive mixtures with air
Vapor Pressure	Not determined
Vapor Density	Not determined
Volatile Organics	Not determined
Density	0.8 mg/cu. cm @ 15.6°C
Solubility	Negligible
K_{ow}	Not determined
Viscosity	1 mm/s ² @ 40°C / 105°F
Autoignition Point	Not determined
Decomposition Temp	Acrylate depolymerization @ 200°C

10. Stability and Reactivity

Stability	Material is normally stable at ambient temperatures and pressures. Has low vapor pressure – vapors may form explosive mixtures with air!
Decomposition Temp	Acrylate depolymerization begins at 200°C
Incompatibility	Keep away from strong oxidizers. Contact with these materials may cause violent or explosive reactions.
Polymerization	Will not occur
Thermal Decomposition	Combustion products highly dependent on conditions. Produces carbon and nitrogen oxides. Lower oxygen environments are likely to produce more harmful particulate carbon, polyaromatic heterocycles, carbon monoxide and other organic compounds.
Conditions to Avoid	Flammable liquid and vapor – keep away from strong oxidizers as well as heat/sparks/open flames/hot surfaces. Do not store at elevated temperatures (< 50°C/122°F).

11. Toxicological Information

	- Acute Exposure –
Eye Irritation	Expected to be irritating to the eyes; 2-Propanol causes eye irritation in rabbits after 24h exposure
Skin Irritation	Mild skin irritant. Repeated exposure may cause dermatitis, drying, cracking, and defatting of the skin.

Respiratory Irritation	Inhalation of vapors or mists may cause irritation to the respiratory system.
Dermal Toxicity	Low order of toxicity LD50 >5g/kg, rat
Inhalation Toxicity	Expected to be of low toxicity if inhaled. Acute inhalation exposure may cause narcotic effects in central nervous system.
Oral Toxicity	Low order of toxicity LD50 >5g/kg, rat
Aspiration Hazard	This product has a very low viscosity and may be fatal if aspirated into the airways. Do NOT induce vomiting, as this increases risk of aspiration/chemical pneumonitis. Aspiration may be fatal.
- Chronic Exposure -	
Chronic Toxicity	This product may cause dryness or defatting of the skin, dermatitis, or may aggravate existing skin conditions.
Carcinogenicity	Limited evidence of carcinogenic effect noted for minor component (Naphthalene). Repeated skin contact has resulted in irritation and skin cancer in animals (Naphthalene)
Mutagenicity	Available information does not suggest that this product is a germ cell mutagen
Reproductive Toxicity	Available information does not suggest that this product is a reproductive toxin.
Teratogenicity	Available information does not suggest that this product is a teratogen
- Additional Information -	
Target organ toxicity	Single Exposure – high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death. Repeat exposure (Kidney) – caused kidney effects in male rats which are not considered relevant to humans Repeat exposure (Kidney) – some evidence of kidney irregularities with repeated exposure of 2-Propanol in humans.
Synergistic effects	No data available
Pharmacokinetics	No data available

12. Ecological Information

- Environmental Toxicity -	
Fish	Toxic: LC/EC/IC50 1 - 10mg/L
Aquatic Invertebrates	Toxic: LC/EC/IC50 1 - 10mg/L
Algae	Toxic: LC/EC/IC50 1 - 10mg/L
Bacteria	Not determined
Microorganisms	Not determined

- Environmental Fate –

Biodegradation	Expected to be readily biodegradable. Oxidizes rapidly by photo-chemical reactions in the air.
Bioaccumulation	Adheres to soil – has the potential to bioaccumulate
Soil Mobility	Adsorbs to soil and has low mobility under normal conditions
Other Effects	Floats on water and produces a sheen – very mobile in the aquatic environment

13. Disposal Considerations**Disposal Considerations**

All disposal practices must be in accordance with local, regional, national, and international regulations. Store material for disposal as indicated in Section 7. Disposal by controlled incineration or recycling may be acceptable – review applicable regulations or regulatory bodies before making disposal decisions.

Contaminated Containers or Packaging

Empty containers are likely to contain flammable vapors or explosive mixtures of vapor and air. Do NOT weld, cut, or grind empty containers. Send to reconditioner or metal reclaimer if possible. Dispose of in accordance with local, regional, national, and international regulations

14. Transportation Information

Description shown may not apply to all shipping situations. Consult applicable shipping codes to determine any additional shipping requirements

US DOT

UN No	1993
UN Proper Name	Flammable Liquid, n.o.s. (contains petroleum distillates, isopropanol, 1,2,4-trimethyl benzene, 2-ethylhexyl nitrate)
UN Class	3
Packing Group	II
Marine Pollutant	*This product is carried under the scope of MARPOL Annex I

IMDG

UN No	1993
UN Proper Name	Flammable Liquid, n.o.s. (contains petroleum distillates, isopropanol, 1,2,4-trimethyl benzene, contains 2-ethylhexyl nitrate)
UN Class	3
Packing Group	II
Environmental Hazard	Yes

ICAO/IATA**UN No**

1993

UN Proper Name

Flammable Liquid, n.o.s. (contains petroleum distillates, isopropanol, 1,2,4-trimethyl benzene, contains 2-ethylhexyl nitrate)

UN Class

3

Packing Group

II

15. Regulatory Information**- Global Chemical Inventories/Regulations -****USA**

All components of this material are on the US TSCA

Other TSCA Reg.

This product is listed on the TSCA as UVCB (Unknown, Variable composition, or Biological)

EU

Components of this product and similar mixtures are registered under REACH. Consult the European Chemicals Agency regarding REACH registration, reporting, and other legal requirements for kerosene before importing to the EU.

Canada

All components of this product are listed on the Canadian Domestic Substances List (DSL).

Canada WHMIS

B2 (Flammable Liquid)

- Other U.S. Federal Regulations -**SARA Ext. Haz. Subst.** No chemicals in this product are listed on the SARA 302 Extremely Hazardous Substances list.**SARA 311/312***Acute Hazard* - YES*Chronic Hazard* - YES*Fire Hazard* - YES*Reactivity Hazard* -**SARA Sect. 313**

This product contains 2-Propanol (CAS # 67-63-0). This product may also contain listed chemicals below the de minimus levels which therefore are not subject to the notification requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act.

CERCLA Haz. Sub.

Solvent naphtha (petroleum), heavy aromatic; kerosene, 1250lbs.

CAA Section 112

Contains Naphthalene (CAS # 91-20-3) listed as a hazardous air pollutant under CAA Section 112.

- State Regulations -**CA Prop 65****Warning:** This product contains a chemical known to the State of California to cause cancer (Naphthalene)

Right to Know Component	Right to Know States
2-Propanol (CAS # 67-63-0)	MA, NJ, PA
Naphthalene (CAS # 91-20-3)	CA, MA, MN, NJ, PA

- Other -

Not determined

16. Other Information

Revision updates may be in many sections and the MSDS should be read in its entirety. Prepared according to the UN Globally Harmonized System for the Classification and Labeling of Chemicals (GHS) by Champion LLC, 1001 Golden Drive, Clinton, Missouri 64735.

Disclaimer: The information presented herein has been compiled from sources considered to be dependable and is accurate to the best knowledge of Champion Brands, L.L.C. Champion Brands, L.L.C., makes no warranty whatsoever expressed or implied of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Champion Brands, L.L.C., assumes no legal responsibility for use or reliance upon this data. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.