



SAFETY DATA SHEET

1. Product Identification

Champion Brands, LLC
1001 Golden Drive
Clinton, MO 64093
(660) 885-8151

Product line: CHAMPION® Micro Sprint Oil
Products: 4445, 4446
CAS: Not applicable (Mixture)
Synonyms: Racing engine oil
Recommended use: Specialty engines
Restrictions: None determined
Created: 8 October 2012
Revised: 22 November 2016
Emergency phone: CHEMTREC: (+1) 800-424-9300

2. Hazards Identification

Appearance: Blue liquid
Odor: Mild Petroleum
Classification: None
Target organs: Not Determined
Symbol(s): None
Signal Word: None
Hazard Statement(s): None
Other hazard(s): Product will burn, though difficult to ignite. This product produces oil sheen on bodies of water. Components of this product are classified as toxic to aquatic life. Mists of sprays of this product may be harmful if inhaled. Used crankcase oil may contain carcinogenic combustion by-products.

Precaution(s): Wear protective gloves/protective clothing/eye protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

Disposal: Keep out of waterways. Check local, national, and international regulations for proper disposal

3. Composition/Information on Ingredients

Hazardous Ingredients:

| <i>Component</i> | <i>CAS No.</i> | <i>Conc (wt%)</i> |
|---|----------------|-------------------|
| Mineral oil | Mixture | 80 – 90 |
| Zinc dialkyldithiophosphate | 68649-42-3 | 1 – 2 |
| Calcium long-chain alkylphenate sulfide | Proprietary | 1 – 2 |
| Alkaryl amine | Proprietary | < 1 |
| Phenol, 4-dodecyl- | 104-43-8 | < 0.1 |

4. First Aid Measures

| | |
|------------------------|--|
| Eyes | Flush eyes with running water for at least 15 minutes. Get medical immediately. |
| Skin | Flush exposed area with running water for at least 15 minutes. Remove contaminated clothing and launder before reuse. Get medical attention if irritation persists or if signs of an allergic reaction appear. |
| Inhalation | Move to fresh air. If nausea or other symptoms persist, get medical attention. |
| Ingestion | DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, lower head below hips to reduce risk of aspiration. If conscious, give one glass of water. Get immediate medical attention |
| Additional Info | Note to physician: Treat symptomatically. Contact poison control for more information. |

5. Fire Fighting Measures

| | |
|---------------------------------|---|
| Flash Point | > 180°C / 356°F (based on flammability of components) |
| NFPA | Health: 1 Fire: 1 Reactivity: 0 |
| Extinguishing Media | Use water spray, fog, foam, dry chemical or CO ₂ |
| Unsuitable Media | Water jet may cause fire to spread |
| Firefighting Procedures: | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear |
| Unusual Hazards | See section 10 for additional information |

6. Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures: Keep unnecessary personnel away. Wear appropriate personal protective equipment for emergency. Ventilate if released in a confined area. Eliminate sources of ignition if it is safe to do so. Wear suitable personal protective equipment and stop the spread of material with adsorbent or socks if safe to do so.

Environmental precautions: Avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways or groundwater. Produces oil sheen on waterways. Toxic to aquatic organisms

Methods for removal: Use a pump or bucket to recover free liquid. Residual liquid can be absorbed on inert material. Use non-sparking tools.

7. Handling and Storage

Max. Handling Temp: 70°C / 158°F

Procedures:

Open container in a cool, well ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Use appropriate containment to avoid environmental contamination. Avoid use in confined areas without adequate ventilation. Areas of inadequate ventilation could contain concentrations high enough to cause eye irritation, headaches, respiratory discomfort or nausea. Avoid breathing dust, fume, gas, mist, vapors, or spray. Wash thoroughly after handling. Launder contaminated clothing before reuse. Empty container contains product residue which may exhibit hazards of the product. Dispose of packaging or containers in accordance with local, regional, national, and international regulations. Store away from strong oxidizers

Max Store Temp: 40°C / 104°F

8. Exposure Controls/Personal Protection

Exposure Limits

Guidelines by component

Mineral Oil (mists)

| | |
|---------------|-------------------------------|
| OSHA TWA: | 5 mg/m ³ |
| ACGIH TWA: | 5 mg/m ³ |
| TWA (Canada) | 5 mg/m ³ |
| STEL (Canada) | 10 mg/m ³ |
| EH40-MEL | 5 mg/m ³ , 8 hours |
| NOHSC | 5 mg/m ³ , 8 hours |

Other Exposure Limits: None known

Engineering Controls: Use in a well ventilated area. Where possible, cover sources of oil sprays and mists with adsorbent cloth to minimize exposure to mineral oil mists. Keep concentrations of mist below exposure limits

Personal Protective Equipment

Respiratory: Where mineral oil mists are generated – use full face respirator with organic vapor cartridge.

Eye: Wear safety glasses where splashing or splattering may occur

Gloves: Use nitrile or neoprene gloves. If material is hot, use appropriately insulated gloves.

Clothing: Use neoprene or nitrile gloves. When handling at elevated temperatures, use insulated apron or coat. Launder contaminated clothing before reuse

Hygiene: Wash thoroughly after handling this product.

9. Physical and Chemical Properties

| | |
|-------------------------------|----------------|
| Appearance | Blue liquid |
| Odor | Mild Petroleum |
| Odor threshold | Not determined |
| pH | Not determined |
| Melting Point | Not determined |
| Initial Boiling Pt/Rng | Not determined |

| | |
|---------------------------|---|
| Flash Point | > 180°C / 356°F (estimated based on components) |
| Evaporation Rate | Nil (where nBuAc = 1) |
| Upper Flammable Lm | Not determined |
| Lower Flammable Lm | Not determined |
| Explosive Data | Not determined |
| Vapor Pressure | Not determined |
| Vapor Density | Not determined |
| Volatile Organics | Not determined |
| Density | 0.9 mg/cu. cm @ 15.6°C |
| Solubility | Insoluble in water, alcohols; soluble in organics |
| K_{ow} | Not determined |
| Viscosity | Varies based on SAE viscosity grade |
| Autoignition Point | Not determined |
| Decomposition Temp | Not determined |

10. Stability and Reactivity

| | |
|------------------------------|---|
| Stability | Material is normally stable at normal temperatures and pressures |
| Decomposition Temp | Not determined |
| Incompatibility | Oxidizers and reducers |
| Polymerization | Will not occur |
| Thermal Decomposition | Smoke, oxides of carbon, nitrogen, phosphorous, boron, sulfur, and metals. May also generate hydrogen sulfide if stored for extended periods of time at elevated temperatures |
| Conditions to Avoid | Keep away from heat, flames, strong oxidizers and strong reducing agents |

11. Toxicological Information

- Acute Exposure -

| | |
|-------------------------------|---|
| Eye Irritation | Contact with the eye will likely cause serious irritation. Symptoms include pain, tearing, reddening, swelling, and impaired vision. If material is hot, thermal burns may occur with eye contact |
| Skin Irritation | Repeated or prolonged exposure causes skin irritation or non-allergic dermatitis. Symptoms may include redness, drying, and cracking of the skin. Heated material may cause thermal burns |
| Respiratory Irritation | May cause nose, throat and lung irritation with mists at elevated temperatures. |
| Dermal Toxicity | Not expected to present a danger of dermal toxicity. |
| Inhalation Toxicity | Inhalation of this product is not expected to be toxic. Exposure to mineral oil mists may be harmful. Symptoms of over-exposure to mineral oil mists may be similar to that of pneumonia. |

| | |
|------------------------------|--|
| Oral Toxicity | Not expected to be harmful. LD50 in rats exceeds 5g/Kg. |
| Aspiration Hazard | This product does not present a classifiable hazard of aspiration due to viscosity – however, this product may be fatal if swallowed and enters airways, particularly in those with weakened respiratory systems. |
| | - Chronic Exposure – |
| Chronic Toxicity | No data available to indicate product or components present at greater than 0.2% are chronic health hazards |
| Carcinogenicity | This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test. |
| Mutagenicity | No data available to indicate product or any components at greater than 0.1% are mutagenic or genotoxic. |
| Reproductive Toxicity | Contains material that may cause adverse reproductive effects with repeated oral exposure based on animal data of components. |
| Teratogenicity | No data available to indicate product or any components at greater than 0.1% may cause teratogenic effects. |

12. Ecological Information

| | |
|------------------------|--|
| | - Environmental Toxicity – |
| Miscellaneous | No LD/LC/EC50 data was collected for this product. Some components of this product are considered toxicants to aquatic life, though at concentration that is not sufficient to require classification as a marine pollutant or aquatic toxicant. |
| | - Environmental Fate – |
| Biodegradation | The petroleum oil in this product is not readily biodegradable, but can be broken down by microorganisms and is therefore considered to be inherently biodegradable. Some components of this product may persist in the environment |
| Bioaccumulation | The petroleum oil in this product has a K_{ow} greater than 5.3 and is regarded as having the potential to bioaccumulate. In practice, metabolic processes may reduce this potential. |
| Soil Mobility | This product is expected to have low soil mobility due to very low water solubility and low vapor pressure. Petroleum oils adsorb to soil and sediment. Once adsorbed, the product is expected to adhere to soil until it is slowly biodegraded. |
| Other Effects | Product will produce oil sheen and float on the surface of bodies of water. The product will spread across the surface as a function of viscosity and velocities of water and surface wind. |

13. Disposal Considerations

Disposal Considerations

All disposal practices must be in accordance with local, regional, national, and international regulations. Do not dispose in a landfill. Wherever possible, recycle product to used oil collection facilities in accordance with applicable regulations.

Contaminated Containers or Packaging

Dispose of packaging or containers in accordance with local, regional, national, and international regulations

14. Transportation Information

Description shown may not apply to all shipping situations. Consult applicable shipping codes to determine any additional shipping requirements

US DOT Not Regulated

*If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil)

UN No Not applicable

UN Proper Name Not applicable

UN Class Not applicable

Packing Group Not applicable

Marine Pollutant *No

*Product contains petroleum oil which may be classified as a marine pollutant under MARPOL Annex I under certain shipping conditions (Contains oil)

IMDG Not Regulated

*U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 25. If transported in bulk by marine vessel in international waters, product is being carried under the scope of MARPOL Annex I.

ICAO/IATA Not Regulated

*U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23, & 24.

15. Regulatory Information

- Global Chemical Inventories -

USA All components of this material are on the US TSCA or are exempt

Other TSCA Reg. None known

EU At least one component is not listed in EINECS but all such components are listed in ELINCS. Contact supplier for information on the inventory status of material.

New Zealand All components are listed or exempted

Canada All components are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List

- Other U.S. Federal Regulations –

SARA Ext. Haz. Subst. This product does not contain greater than 1.0% of any chemical on the SARA Extremely Hazardous Substances list.

SARA Sect. 311/312

| | |
|--------------------------|-------|
| <i>Acute Hazard</i> | - YES |
| <i>Chronic Hazard</i> | - YES |
| <i>Fire Hazard</i> | - NO |
| <i>Reactivity Hazard</i> | - NO |

SARA 313 Zink dialkyldithiosphosphate; Lead

- State Regulations –

CA Prop 65 WARNING! This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm: Arsenic, Lead, Cadmium.

| <i>Right to Know Component</i> | <i>Right to Know States</i> |
|--|------------------------------------|
| Zinc dialkyldithiosphosphate (CAS # 68649-42-3) | NJ |

16. Other Information

Revision updates may be in many sections and the MSDS should be read in its entirety. Prepared according to the UN Globally Harmonized System for the Classification and Labeling of Chemicals (GHS) by Champion LLC, 1001 Golden Drive, Clinton, Missouri 64735.

Disclaimer: The information presented herein has been compiled from sources considered to be dependable and is accurate to the best knowledge of Champion Brands, L.L.C. Champion Brands, L.L.C., makes no warranty whatsoever expressed or implied of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Champion Brands, L.L.C., assumes no legal responsibility for use or reliance upon this data. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.