



CHAMPION PROFESSIONAL GRADE SNOW PLOW OIL

Champion Professional Grade Snow Plow Oil is a long-life hydraulic oil formulated with severely hydrotreated and hydrofinished API Group II base oils for improved oxidation resistance, viscosity retention and cold flow properties. This oil has excellent viscosity retention and cold-flow due to a very high viscosity index. Excellent protection against wear, corrosion and the build-up of sludge and varnish in the most demanding snowplow applications.

- Extended fluid life for longer service intervals
- Excellent filterability and cleanliness
- High thermal and oxidation stability
- Excellent demulsibility and air release
- Top-tier anti-wear performance
- Excellent cold-flow properties
- Forms thicker films at higher temperatures



Champion Professional Grade Snow Plow Oil meets or exceeds the following specifications:

- Parker (Denison) HF-0, HF-1, HF-2
- MAG (CM) P-68 (ISO 32), P-69 (ISO 46), P-70 (ISO 68)
- GM LS-2
- Joy HO-T, HO-S, HO-T2
- AIST (US Steel) 126, 127
- DIN 51524-3, Type HLVP
- ASTM D6158, Type HV
- ISO 6743/4, Type HV
- Eaton M-2950-S, I-286-S3
- Bosch Rexroth RE 90220
- SEB 181222
- AFNOR NF E 48-603 (HV)
- SAE MS 1004, Type HV
- ANSI/AGMA 9005-E02-RO
- ISO 11158, Type HV

TYPICAL PROPERTIES

Kinematic Viscosity @ 40°C	14.56
Kinematic Viscosity @ 100°C	4.25
VI	224
Density #/gal	7.4
API Gravity	27.8

PART#4013

Available in quarts / gallons

