



#4240 PRESERVATIVE OIL

CHAMPION SUPER GRADE PRESERVATIVE OIL is a corrosion inhibited oil designed for use in preservative oil applications where the product is applied directly onto the surface to be protected. It exhibits excellent humidity resistance as measured in a condensing humidity cabinet ASTM D 1748 and ASTM D 2247 Humidity Test. It additionally displaces moisture and gives protection against the extreme corrosiveness of salt spray. It has excellent anti-staining properties and can be readily removed using conventional methods. Commercial automotive alkaline cleaner is the preferred method of removing residue.

CHAMPION SUPER GRADE PRESERVATIVE OIL has excellent cold temperature characteristics making it suitable for use in low ambient temperature conditions.

TYPICAL SPECIFICATIONS

Product Code	4240
Gravity API @ 60° F	33.2
Viscosity:	
cSt @ 40° C	20.33
cSt @ 100° C	4.07
Viscosity Index	95
Pour Point ° F	-20
Flash Point ° F	380
ASTM D 2247	
Cleveland Condensing Humidity Test	none
% Rusted Area	
ASTM D 1748 40 Days Jan-H-729 Humidity Test	1000+
Cleanability Test Alkaline Cleaner	pass
Color ASTM	2.0

Available in:

#4240A - 55 gallon

#4240D - 5 gallon