



#4314 SAE 75W90  
 #4315 SAE 80/140  
 GEAR LUBE  
 HTS SYNTHETIC

CHAMPION HTS GEAR LUBRICANT is a 100% synthetic gear lubricant, blended with “state of the art” additives. This special blend features a high viscosity index and low pour point, complimented with additives that offer extreme pressure, rust, corrosion, and oxidation protection. Under normal conditions, CHAMPION HTS GEAR LUBE can extend gear life, improve fuel mileage, and provide easier shifting at low temperatures, which helps reduce maintenance downtime. When extreme conditions exist, CHAMPION HTS GEAR LUBE excels, providing further protection.

Recommended for manual transmissions requiring an EP lubricant, conventional and limited slip differentials, and transfer cases in cars, trucks, tractors, and heavy duty equipment requiring a GL5 lubricant.

CHAMPION HTS GEAR LUBRICANT is Eaton approved, and exceeds GL5, military MIL-L-2105D, Eaton 88-102, General Electric D50E9C, Harnischfeger 474, Mack GL/G/S, and Rockwell 076E.

TYPICAL SPECIFICATION

	4314	4315
Product Code	4314	4315
SAE	75W90	80W140
Gravity API @ 60° F	29.7	30.1
Viscosity		
cSt @ 40° C	117.1	312
cSt @ 100° C	15.6	31.3
cSt @ -26° C		80,000
cSt @ -40° C	109,000	
Viscosity Index	139	139
Pour Point ° F	-54	-44
Flash Point ° F	405	425
AGMA Grade	4 EP	5-6 EP

Available in:

#4314A - 410# drum	#4315A - 410# drum
#4314C - 120# drum	#4315C - 120# drum
#4314D - 35# pail	#4315D - 35# pail