



DIESEL FUEL CONDITIONER AND ANTIGEL

TACKLES FUEL DEPOSITS, REMOVES WATER, AND PREVENTS DIESEL GEL.

Improves cold flow and prevents freezing. Cleans fuel system and restores power while stabilizing fuel.

This superior formula is specifically designed to meet the needs of diesel engines. It is a "Clean Up and Keep Clean" formula that also conditions both ULSD and bio-diesel fuel by removing water and stabilizing them against filter plugging at cold temperatures. Super concentrated, treats up to 40 gallons.

DIRECTIONS: Use with every tank fill-up to either clean up or maintain a clean fuel system, or to help prevent diesel fuel from gelling or freezing up. Safe and effective for use in all diesel engines. Meets EPA requirements for use in ULSD fuel.

Order Information:

Part #	Container	Case Qty
49551	16 fl. oz.	8
Case Dimensions L x D x H (in)	Case Weight (lbs.)	
3.7x2x9.6	8.4	

Typical Values:

Product Code	49551
MSDS #	49551
API Gravity	43.4 @ 60°F
Appearance	Clear
Physical State	Liquid
Boiling Point, °F	Not Determined
Evaporation Rate	<1.00 (Butyl Acetate)
Vapor Pressure	Not Determined
pH	Not Determined
Solubility	Not Soluble in water
VOC	100% 787.0 g/l, 6.560
Color	Amber
Odor	Petroleum



49551

Effective 05/09

CHAMPION BRANDS, L.L.C. › 1001 GOLDEN DRIVE › CLINTON, MO 64735
ORDER DESK 800-821-5693