2 Cycle Oil
POWER EQUIPMENT

2 CYCLE OIL POWER EQUIPMENT is our premium quality ashless motor oil for use in 2-cycle air cooled engines. This specially formulated oil meets the lubrication and high temperature demands of air cooled engines by combining Group II base oil and pure isobutene, rather than commonly used fragmented isobutylene which can degrade faster at high temperature. In addition, it contains several semi-synthetic additives providing excellent detergency and dispersant to provide protection and performance requirements of leading engine manufacturers including;

- BOLENS
- CRAFTSMAN
- CUB CADET
- ECHO
- HOMELITE
- HONDA
- HUSQVARNA
- IDC
- JOHN DEERE
- LAWNBOY
- MAKITA
- McCULLOUGH
- RED MAX
- ROBIN SOLO
- RYAN
- RYOBI
- SHINDAIWA
- STIHL
- TANAKA
- TMC
- TORO
- TROY BILT
- WEEDEATER

Additional benefits include:

- Super tough film oil protects against engine wear, and corrosion.
- Anti-foaming and superior anti-scuffing protection
- Increases performance by reducing engine deposits, carbon and spark plug fouling
- Blended to provide anti-smoke performance to meet any state, national, or international regulatory requirements

Recommended for use where manufacturer specifications require 2-Cycle oil meeting performance requirements of;

- **API TC**
- **JASO FD**
- **ISO-L-EGD**
- **TISI**

Mix only according to the manufacturer's recommended mixing ratio.

TYPICAL PROPERTIES

Product Code	**4115**
MSDS #	200
Color	Green
Gravity API @ 60°F	32.9
cSt @ 40°C	46.8
cSt @ 100°C	8.4
SUS @ 104°F	315
SUS @ 210°F	54
Viscosity Index	150
Pour Point °F	-37
Flash Point °F	140

Call Our Friendly Sales Representatives for Available Package Sizes

4115 **EFFECTIVE 11/08**

Distributed by
CHAMPION OILS • 270 N. Vinedo • Pasadena, CA 91107
ORDER DESK 800-222-5823