

## Purpose Built Performance

Champion® Racing Motor Oils are purpose built products designed for severe racing applications. These products contain Champion's proprietary TVS® (Thermal Viscosity Stabilizer), special lubricity modifiers, and a premium level of anti-wear additives which includes a high quantity of ZDDP. These additives are proven to meet the lubrication demands of competition engines, create a tough film strength, which controls wear and provides more horsepower and torque in Dynamometer testing.

Champion® Racing Oils are suitable for use in all competition engines especially those using flat tappet and/or roller cams operating at high RPMs and requiring high-pressure (stiff) valve springs. These products are offered in a popular range of multi-viscosity SAE grades and formulated to meet the demands of most of today's high performance race engines.

## Features:

- Provides exceptional low coefficient of friction
- Offers film strength and viscosity stability at higher temperatures
- Formulated for the protection of flat tappet cams, roller cams and bearings in turbo and super-charged racing engines Increases high-temp oil pressure and compression
- Compatible with all racing fuels including methanol
- Provides upper cylinder anti-wear protection
- Reduces engine oil temperature
- Compatible with other petroleum and synthetic oils

| Typical Properties   |           |           |
|----------------------|-----------|-----------|
| SAE                  | 10W-30    | 20W-50    |
| Part #               | 4104H     | 4111H     |
| MSDS #               | 100       | 100       |
| Color                | Blue      | Blue      |
| Lbs./Gal.            | 7.19      | 7.29      |
| Gravity              | 0.864     | 0.876     |
| Viscosity@100°C, cSt | 11.0      | 19.0      |
| Anti-wear Elements   |           |           |
| Zn, %wt              | 0.160     | 0.160     |
| Ca, %wt              | 0.200     | 0.200     |
| Mo, %wt              | 0.090     | 0.090     |
| Flash Pt., °C (°F)   | 227 (440) | 232 (450) |
| Pour Pt., °C (°F)    | -37 (-34) | -29 (-20) |

Not recommended for radial piston racing engines.



FOR MORE INFORMATION, CALL (800) 821-5693 Champion Brands, LLC,

1001 Golden Drive, Clinton MO 64735



## **Applications:**

Use for lubrication of high-performance competition supercharged, turbocharged, injected, and naturally aspirated four-cycle engines using high octane gasoline or other exotic fuels (including methanol or nitromethane).