



R&O Vacuum Pump Fluid

CHAMPION R&O VACUUM PUMP FLUID is a great general-purpose rust and oxidation inhibited fluid for use wherever R&O inhibited anti-wear lubricants are specified. It is the lubricant of choice for many users because of its reputation for long life, excellent equipment protection and outstanding versatility in the wide variety of marine and industrial applications. Used widely in steam and hydro turbines with splash, bath and ring-oiling arrangements, and all other continuous circulation methods involving pumps, valves, moderate pressure hydraulic systems and ancillary equipment. Recommended for continuous service in the lubrication of plain and rolling bearings and parallel shaft gearing. It has been used successfully in vacuum pumps, turbine and rotary air compressor applications.

Meet performance requirements for:

- Denison HF-O and HF-2
- Vickers industrial & mobile applications
- Cincinnati Milacron P-68, P-69, and P-70

TYPICAL SPECIFICATION

ISO Grade	32
Product Code	4153N
MSDS #	1200
Color	Clear
Gravity API @ 60° F	30.6
cSt @ 40°C	31.7
cSt @ 100°C	5.3
SUS @ 100°F	150
SUS @ 210°F	45
Viscosity Index	95
Pour Point ° F	-24
Flash Point ° F	402
Dielectric Strength, D-877, kV	52

Call Our Friendly Sales Representatives for Available Package Sizes

4153N

EFFECTIVE 04/05