



Premium HD 15W-40 MOTOR OIL

Champion Premium HD 15W-40 engine oil is designed to provide robust performance to meet the needs of the next generation of heavy duty engines. Increased power density, reduced oil volume and extended drain intervals place unique demands on engine oils to control oxidation by-products, sludge and deposits. Due to higher shear stress and lower viscosity minimums for engine oils, only oils with the highest wear protection and viscosity stability can maximize the performance and life of advanced diesel engines.

Oxidation Control- Champion Premium Heavy Duty® engine oil takes oxidation resistance to another level, allowing users to achieve longer drain intervals, reduce maintenance and downtime, and extend engine life. Controlling oxidation, corrosive acids, sludge and varnish precursors allows for extended drains and minimized wear even under the most extreme conditions.

- Oxidation lower than OEM limits in over 60,000 mile on-highway and 600 hour off-highway drain intervals
- Robust additives provide over 45% better oxidation resistance than CK-4 limits on Volvo T-13

Wear Control- Champion Premium Heavy Duty® engine oil delivers value keep your engines going longer by reducing engine wear, preventing high temperature corrosion and controlling abrasive soot contamination. Higher resistance to permanent shear loss and exceptional wear protection provide unmatched value for many diesel fleets.

Champion Premium Heavy Duty® Oils meet or exceed the following specifications:

- API CK-4, CJ-4, CI-4 Plus
- JASO DH-2
- Cummins CES 20086
- Cummins CES 20081
- Ford WSS-M2C171-F1
- Mack EO-O Premium Plus
- ACEA E7-16, E9-16
- Volvo VDS-4.5, VDS-4
- Detroit Diesel DFS93K218
- Detroit Diesel DFS93K222
- Renault VI RLD-3
- CAT ECF-3

Part Number	Method	SAE 15W-40
Part Number		4152
Viscosity @ 40°C, cSt	D445	15.5
Viscosity @ 100°C, cSt	D445	120
Viscosity Index	D2270	135
Cold-Cranking Viscosity, cP	D5293	6,400 @ -20°C
Pumping Viscosity, cP	D4684	23,000 @ -25°C
HTHS @ 150°C, cP	D4683	4.3
NOACK Volatility, %	D5800	10
Zinc, ppm	D4951	1250
Phosphorous, ppm	D4951	1140
Oxidation Resistance, mins	D6186	249*
TBN, mgKOH/g	D2896	10

*PDSC data collected for SAE 10W-30, API CK-4 viscosity grade

**Typical properties; does not constitute a specification



EFFECTIVE 07/16

CHAMPION BRANDS, L.L.C. › 1001 GOLDEN DRIVE › CLINTON, MO 64735
ORDER DESK 800-821-5693