



CHAMPION RACING FUEL

CHAMPION® Racing Fuels are premium quality high octane, leaded fuels for use at the race track. Champion® Racing Fuels are non-oxygenated and have low sulfur content. They are available in three octane grades.

Because Champion® Racing Fuels contain tetraethyl lead they are not legal for on-street use. Please review Safety Data Sheet before handling.

Harmful to catalytic converters and oxygen sensors. May cause irreversible damage to catalytic emission reduction devices and on-board sensors.

Typical Properties:

	CRF111	CRF114	CRF118
API Gravity	62.3	62.3	70.6
Specific Gravity @ 15.6°C/60°F	0.73	0.73	0.70
Sulfur, ppm	5	5	5
Motor Octane Number	105.6	107.0	113.0
Anti-Knock Index	111.0	113.0	114.0
Copper Corrosion, max	1B	1B	1B



CRF111

KEEP OUT OF REACH OF CHILDREN

HAZARDS: EXTREMELY FLAMMABLE. Vapors may cause flash fires or ignite explosively. Harmful or fatal if swallowed. May be aspirated into lungs if swallowed. May be harmful to the blood, reproductive and nervous systems.

PRECAUTIONS: Unleaded gasoline has produced cancer in laboratory animals and kidney disease in male rats. Keep away from heat, spark flame and ignition sources. Close container tightly after each use. Store only in closed container. Use with adequate ventilation. Prevent vapor buildup. Do not store indoors. Avoid prolonged contact with skin. Avoid breathing vapors. Avoid contact with eyes.

FIRST AID: IF SWALLOWED, DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY. A physician may, at his discretion, perform gastric lavage using a cuffed endotracheal tube. In case of eye contact, flush eyes with running water for at least 15 minutes. If irritation develops, seek medical attention. Promptly wash skin with soap and water. Remove soiled clothing. Launder clothing before reuse. If inhaled, remove to fresh air. If breathing ceases, administer artificial respiration followed by oxygen.

Visit www.championbrands for Safety Data Sheet