



ALLTRANS™

Full Synthetic Automatic Transmission Fluid

Champion® AllTrans™ Full Synthetic ATF is a universal fluid of exceptional quality. Formulated for use in automatic transmissions, Champion AllTrans Full Synthetic ATF's carefully balanced frictional properties offer smoother shifting and excellent anti-shudder performance in a wide variety of domestic and import passenger cars and light trucks. AllTrans Full Synthetic ATF also offers exceptional shear stability, superior wear protection, and longer fluid service life. This 100% synthetic fluid provides significant protection against sludge and varnish buildup, remarkable thermal stability and oxidation resistance at high temperatures, and better low temperature properties than conventional automatic transmission fluids. This is a truly diverse automatic transmission fluid delivering premium performance and protection in most transmissions used by automobile manufacturers such as Ford, GM, Chrysler, Toyota, Honda, Lexus and others.

Champion® AllTrans™ Full-Synthetic ATF

meets or exceeds the requirements of:

- Allison C-4
- Caterpillar TO-2 (obsolete)
- Chrysler ATF+3, ATF+4 Specifications
- Denison HF-0
- Ford MERCON® V, MERCON®, WSS-M2C924-A Specifications
- GM DEXRON®-III (H), DEXRON®-II, 9986195 Specifications
- Honda Z-1
- JWS 3309 Specification
- Mitsubishi/Hyundai Diamond SP II & III
- Saab 309
- Sundstrand Hydrostatic Transmissions
- Toyota T-IV or T4, T-III or T3 Specifications
- Vickers M-2950-S and I-286-S
- Voith DIWA Transmissions
- ZF Ecomat Transmissions

Champion® AllTrans™ Full-Synthetic ATF

Is the recommended replacement fluid for;

Audi	PN G-052-025-A2
Ford	PN XT-8-QAW
General Motors	PN 88900925
Toyota	PN 08886-00405
Toyota/Lexus/Scion	PN 08886-81015
Porsche	PN 000 043 205 28
Saturn	PN 22689186
Volvo	PN 1161540-8

TYPICAL PROPERTIES

	AllTrans™ ATF
SAE Grade	20W
Product Code	4356
MSDS #	400
Gravity API @ 60°F	29.7
cSt @ 40°C	36.7
cSt @ 100°C	7.6
cP @ -20°C	1,320
cP @ -30°C	3,900
cP @ -40°C	12,900
SUS @ 104°F	166
SUS @ 210°F	50
Viscosity Index	181
Pour Point °F	-50
Flash Point °F	420
Color	Red

WARNING:

DO NOT USE IN PLACE OF

- GM Dexron® VI Transmission Fluid (2006 MY Hydra-Matic transmissions)
- Ford Mercon® SP Transmission Fluid
- Ford Mercon® CVT Transmission Fluid
- Ford Type F Transmission Fluid

Call Our Friendly Sales Representatives for Available Package Sizes