

#4019 SAE 75 #4047 SAE 90 #4120 SAE 80/90 #4157 SAE 85/140 HD ALL PURPOSE GEAR LUBE

CHAMPION HEAVY DUTY ALL PURPOSE GEAR LUBE GL-5 is a high VI gear lube which is manufactured from the finest quality select paraffinic base lubricating oil stocks available. These stocks are then blended with premium additives to exacting specifications, resulting in one of the finest gear lubricants available today. It has an ability to "cling" to the gears even under high speed, over the road operations and has exceptional cold flow characteristics for quicker lubrication under even the most severe weather conditions. Its ability to cling to the gears when the unit is not in use minimizes run-off thereby affording almost instantaneous lubrication when the unit is started.

<u>CHAMPION HEAVY DUTY ALL PURPOSE GEAR LUBE GL-5</u> exceeds the requirements of API service classification GL-5, as well as all major transmission, final drive and gear manufacturers' requirements where a compounded gear lube is recommended.

## TYPICAL SPECIFICATIONS

Product Code:	4119	4047	4120	4157
SAE	75W	90	80W90	85W140
Gravity API @ 60°F	29	26.5	26.9	26.1
Viscosity:				
cSt @ 40° C	49.5	170	140	340
cSt @ 100° C	6.9	16.0	14.6	25.5
Viscosity Index	102	100	101	100
Pour Point ° F	-35	-20	-28	10
Flash Point ° F	390	430	425	435

\_\_\_\_\_\_\_

## Available in:

#4119C - 16 gallon	<u> </u>	#4120A - 55 gallon #4120C - 16 gallon	#4157A - 55 gallon #4157C - 16 gallon
	# 10 17 G 2/2.0 gallon	#4120D - 5 gallon #4120N - 4/1 gallon	#4157D - 5 gallon #4157N - 4/1 gallon
		#4120U - 2/2.5 gallon	#4157U - 2/2.5 gallon

4119/4120/4047/4157 EFFECTIVE 0500