

**CHAMPION ALL FLEET G** premium heavy duty gear lubes are blended with high quality base oils and an optimized additive system to meet the most demanding warranty requirements. They will provide excellent protection in heavy-duty axles and final drives where extreme pressures and shock loading are expected. In addition, they also provide excellent chemical and thermal stability and good performance at low ambient temperatures in combination with excellent corrosion protection.

## Benefits include:

- High thermal stability and oxidation resistance to reduce maintenance costs
- Protection against low speed/ high torque wear
- Excellent rust and corrosion protection under tough operating conditions
- Effective low temperature fluidity to reduce wear and ease start-up of equipment
- Good foam control to improve lubrication and extend seal life
- Multi-grade fluids promote universal versatility with high shear rate protection.

Approved for use in manual transmissions requiring an EP lubricant, conventional, or limited slip differentials, and transfer cases in cars, trucks, tractors, and heavy duty equipment requiring API GL-5, MT-1, Mack GO-J, MIL-PRF-2105E, and PG-2 limited slip lubricant specifications.

## **TYPICAL PROPERTIES**

SAE Grade	80W 90	85W140
Product Code	4216	4217
MSDS #	700	700
Gravity API @ 60°F	27.3	26.2
cSt @ 40°C	139	345
cSt @ 100°C	14.8	27.0
SUS @ 104°F	644	1600
SUS @ 210°F	77	129
Viscosity Index	107	104
Pour Point °F	-25	3
Flash Point °F	485	495
AGMA 9005 EP	Х	Χ
API GL-5, MT-1	Х	Х
Mack GO-J/H/G	Х	Χ

Call Our Friendly Sales Representatives for Available Package Sizes

4216 4217 EFFECTIVE 02/05