



#4314 SAE 75W90
#4315 SAE 80/140
GEAR LUBE
HTS SYNTHETIC

CHAMPION HTS GEAR LUBRICANT is a 100% synthetic gear lubricant, blended with “state of the art” additives. This special blend features a high viscosity index and low pour point, complimented with additives that offer extreme pressure, rust, corrosion, and oxidation protection. Under normal conditions, **CHAMPION HTS GEAR LUBE** can extend gear life, improve fuel mileage, and provide easier shifting at low temperatures, which helps reduce maintenance downtime. When extreme conditions exist, **CHAMPION HTS GEAR LUBE** excels, providing further protection.

Recommended for manual transmissions requiring an EP lubricant, conventional and limited slip differentials, and transfer cases in cars, trucks, tractors, and heavy duty equipment requiring a GL5 lubricant.

CHAMPION HTS GEAR LUBRICANT is Eaton approved, and exceeds GL5, military MIL-L-2105D, Eaton 88-102, General Electric D50E9C, Harnischfeger 474, Mack GL/G/S, and Rockwell 076E.

TYPICAL SPECIFICATION

Product Code	4314	4315
SAE	75W90	80W140
Gravity API @ 60° F	29.7	30.1
Viscosity		
cSt @ 40° C	117.1	312
cSt @ 100° C	15.6	31.3
cSt @ -26° C		80,000
cSt @ -40° C	109,000	
Viscosity Index	139	139
Pour Point ° F	-54	-44
Flash Point ° F	405	425
AGMA Grade	4 EP	5-6 EP

=====
Available in:

4314A - 410# drum	4315A - 410# drum
4314C - 120# drum	4315C - 120# drum
4314D - 35# pail	4315D - 35# pail

4314/4315

EFFECTIVE 1100