

**CHAMPION SUPER CETANE IMPROVER AND CONDITIONER** is a concentrated formula which will upgrade the power and performance of all diesel engines.

**CHAMPION SUPER CETANE IMPROVER AND CONDITIONER**, when mixed at the recommended concentration, will increase the Cetane of any fuel by as much as seven full numbers.

CHAMPION SUPER CETANE IMPROVER AND CONDITIONER is designed to be used as a bulk treatment for both low sulfur (on highway) and high sulfur (off highway) diesel fuel. In addition to raising the cetane rating, it contains a corrosion inhibitor and anti-wear additive which both lubricate and protect the fuel pump and related components against corrosion. This is exceedingly important with the introduction of the new low sulphur fuels which lack the lubricity characteristics that the high sulphur fuels had. It meets the requirements of ASTM D5001 BOCLE test. For use in:

- \* Commerical Vehicles; On and Off Highway
- \* Passenger Cars, Pick-up Trucks
- \* Stationary Equipment
- \* Railroad Locomotives
- \* Marine High-Speed Applications
- \* Agricultural Applications

## Benefits:

- Easier Cold Weather Starting
- \* Faster Warm-Up
- \* Smoother, Quieter, Severe Duty Operation
- \* Reduces Misfiring at Lower Inlet Air Temperatures
- Better Combustion, Fewer Emissions at Light-Duty Operations
- \* Prevents Corrosion
- Contains Lubricity Additive
- \* Meets ASTM D5001 BOCLE test requirements

**CHAMPION SUPER CETANE IMPROVER AND CONDITIONER** is completely soluble in dyed fuels. It can be blended into fuels in the terminal tanks, tank trucks, and underground storage tanks. The same care should be exercised, as with any fuel additive, to ensure good mixing with the fuel.

For best results, mix with diesel fuel which is above 32°F. Store **SUPER CETANE IMPROVER** at 60°F, or higher, is possible.

\_\_\_\_\_

Available in:

#4334A - 55 gallon #4334B - 30 gallon #4334D - 5 gallon

4334 EFFECTIVE 0598